

TECHNICAL DATA

GF

Date 12/22/15

Series 32GF21.0

MOTOR SPECIFICATIONS

Motor Design	Air Filled
Applications	Waste Water
Insulation Class	Class B
Maximum Liquid Temp	0-40 C (32 - 104 F)
Frequency	60 HZ
RPM	3420

PUMP & MOTOR DATA

Impeller	Vortex
Cutter Ring	SUS440C
Discharge	1.25
Motor	2 Pole
KW /Hp	1.0 / 1.5 HP
Phase	1 & 3
Cable	VCT or SJOW/SOW 33 Ft
Protection	Auto Cut

MATERIALS OF CONSTRUCTION

Motor Housing	FC-200
Impeller	FC-200
Volute	FC-200
Rotor	SUS 403
Hardware	316 SS
O-Rings	BUNA"N"
Upper Bearing	Roller Bearing
Lower Bearing	Roller Bearing
Mechanical Seal	Silicon/Silicon
	Carbon /Ceramic

DIMENSIONS, WEIGHT

Pump weight	62 LBS
Maximum Submergence	100 Ft
Optional	Float Switch

Model	32GF21.0	1Ph	1Ph	3 Ph	3 Ph	3 Ph
		115	230	230	460	575
Amps		6.2	4	2	1.6	