

TECHNICAL DATA

GF

Date 12/22/15

Series 50GF22.2

MOTOR SPECIFICATIONS

Motor Design	Air Filled
Applications	Waste Water
Insulation Class	Class B
Maximum Liquid Temp	0-40 C (32 - 104 F)
Frequency	60 HZ
RPM	3470

PUMP & MOTOR DATA

Impeller	Vortex
Cutter Ring	SUS440C
Discharge	2"
Motor	2 Pole
KW /Hp	2.2 / 3 HP
Phase	1&3
Cable	VCT or SJOW/SOW 33 Ft
Protection	Auto Cut

MATERIALS OF CONSTRUCTION

Motor Housing	FC-200
Impeller	FC-200
Volute	FC-200
Rotor	SUS 403
Hardware	316 SS
O-Rings	BUNA"N"
Upper Bearing	Roller Bearing
Lower Bearing	Roller Bearing
Mechanical Seal	Silicon/Silicon
	Carbon /Ceramic

DIMENSIONS, WEIGHT

Pump weight	113 LBS
Maximum Submergence	100 Ft
Optional	

Model	50GF22.2	1Ph	1Ph	3 Ph	3 Ph	3 Ph
		115	230	230	460	575
Amps		18.6	10	5	4	