

TECHNICAL DATA

AF

Date 12/22/15

Series 80AFU22.2L

MOTOR SPECIFICATIONS

Motor Design	Air Filled
Applications	Waste Water
Insulation Class	Class B
Maximum Liquid Temp	0-40 C (32 - 104 F)
Frequency	60 HZ
RPM	3450

PUMP & MOTOR DATA

Impeller	Vortex
Solid Size	3"
Discharge	3"
Motor	2 Pole
KW /Hp	2.2/ 3 HP
Phase	1 & 3
Cable	VCT or SJOW/SOW 33 Ft
Protection	Auto-Cut

MATERIALS OF CONSTRUCTION

Motor Housing	FC-200
Impeller	FC-200
Volute	FC-200
Rotor	SUS 403
Hardware	316 SS
O-Rings	BUNA"N"
Upper Bearing	Roller Bearing
Lower Bearing	Roller Bearing
Mechanical Seal	Silicon/Silicon
	Carbon /Ceramic

DIMENSIONS, WEIGHT

Pump weight	99 LBS
Maximum Submergence	100 Ft
Optional	Float Switch

Model	80AFU22.2L	1Ph	1Ph	3 Ph	3 Ph	3 Ph
		115	230	230	460	575
Amps			14.2	8.4	4.2	