

TECHNICAL DATA

80SFP23.7

Date 12/22/15

Series SF

MOTOR SPECIFICATIONS

Motor Design	Air Filled
Applications	Waste Water
Insulation Class	Class F
Maximum Liquid Temp	0-40 C (32 - 104 F)
Frequency	60 HZ
RPM	3460

PUMP & MOTOR DATA

Impeller	Semi-open P type
Solid	1.25"
Discharge	3"
Motor	2 Pole
KW /Hp	3.7 kW / 5 Hp
Phase	3
Cable	VCT or SJOW/SOW 33 Ft
Protection	Auto Cut

MATERIALS OF CONSTRUCTION

Motor Housing	SCS14	
Impeller	SCS14	
Volute	SUS 316	
Rotor	SUS 316	
Hardware	SUS 316	
O-Rings	Viton	
Upper Bearing	Ball Bearing	
Lower Bearing	Ball Bearing	
Mechanical Seal	Lower	Silicon / Silicon
	Upper	Carbon / Ceramic

DIMENSIONS, WEIGHT

Pump weight	119 lbs.
Maximum Submergence	100 Ft.
Optional	

Model	80SFP23.7	1Ph	1Ph	3 Ph	3 Ph	3 Ph
		115	230	230	460	575
Amps				13.6	6.8	