

# TECHNICAL DATA

A

Date 12/22/15

Series AN-21

## MOTOR SPECIFICATIONS

Motor Design	Air Filled
Applications	Effluent water
Insulation Class	Class B
Maximum Liquid Temp	0-40 C ( 32 - 104 F )
Frequency	60 HZ
RPM	3400

## PUMP & MOTOR DATA

Impeller	Semi Open
Solid Size	1/4"
Discharge	2"
Motor	2 Pole
KW /Hp	.75 / 1 hp
Phase	1 & 3
Cable	VCT or SJOW/SOW 23 Ft
Protection	Auto Cut

## MATERIALS OF CONSTRUCTION

Motor Housing	SUS 304
Impeller	FC-200
Volute	FC-200
Rotor	SUS 410
Hardware	316 SS
O-Rings	BUNA"N"
Upper Bearing	Roller Bearing
Lower Bearing	Roller Bearing
Mechanical Seal	Silicon /Silicon
	Carbon /Ceramic

## DIMENSIONS, WEIGHT

Pump weight	38 Lbs
Maximum Submergence	100 Ft
Optional	Float Switch

Model	AN-21	1Ph	1Ph	3 Ph	3 Ph	3 Ph
		115	230	230	460	575
Amps		10.0	5.0	3.4	1.7	