

MODEL:

IF12250/6-470

MATERIALS	
Volute	ASTM-A48 CL-30
Impeller	ASTM-A48 CL-30
Main shaft	410 SS
Upper seal	Carbon-ceramic
Lower seal	*Carbon-ceramic
Bolts and nuts	18-8 SS
Wear ring	Bronze
Handle	304 SS
Coating	Epoxic Carbon

* Silicon Carbide (SIC) optional

REF.	in	mm
A'	41.9	1066
B'	3.9	100
C'	32.6	830
D'	55.8	1418
E'	31.1	790

Pump Height		
HP	in	mm
250	92.5	2350

Pump Weight		
HP	Lbs	Kg
250	4409.2	2000

REF.	in	mm
A	2.9	76
B	0.8	21
C	11.5	293
D	4	102
E	52.1	1324
F	73.4	1865
G	38.1	970
H	23.4	595
I	24.6	625
J	3.8	97
K	0.9	23
L	12.2	311
M	76.9	1954
N	6.0	152
O	20.5	520
P	17.5	445
Q	12.5	317
R	8.7	220
S	18.5	470
T	16.0	406
U	34.5	876
V	40.2	1022
W	23.9	608
X	16.3	415
Y	40.3	1023
Z	73.7	1873

