

## MODEL: IF1250/6-302, IF1260/6-310, IF1275/6-330 & IF12100/6-345

MATERIALS	
Volute	ASTM-A48 CL-30
Impeller	ASTM-A48 CL-30
Main shaft	410 SS
Upper seal	Carbon-ceramic
Lower seal	Carbon *Carbon-ceramic
Bolts and nuts	18-8 SS
Wear ring	Bronze
Handle	304 SS
Coating	Epoxic

\* Silicon Carbide (SiC) optional

REF.	in	mm
A`	41.9	1066
B`	3.9	100
C`	32.6	830
D`	45.4	1155
E`	30.7	780

Pump Height		
HP	in	mm
50	60.8	1546
60		
75		
100	62.9	1600

Pump Weight		
HP	Lbs	Kg
50	1058.2	480
60	1102.3	500
75	2204.6	1000
100	2645.5	1200

REF.	in	mm
A	3.0	76
B	0.8	21
C	11.5	293
D	4	102
E	47.6	1210
F	56.6	1440
G	38.2	970
H	23.4	595
I	24.6	625
J	3.8	97
K	0.9	23
L	15.5	395
M	73.6	1870
N	5.9	152
O	20.4	520
P	17.5	445
Q	12.4	317
R	8.6	220
S	16.	409
T	11.7	298
U	27.8	707
V	33.8	860
W	23.2	590
X	13.7	350
Y	37	940
Z	66.9	1700

