

MODEL: IF640/4-250, IF650/4-268 & IF660/4-285

MATERIALS	
Volute	ASTM-A48 CL-30
Impeller	ASTM-A48 CL-30
Main shaft	410 SS
Upper seal	Carbon-ceramic
Lower seal	*Carbon-ceramic
Bolts and nuts	18-8 SS
Wear ring	Bronze
Handle	304 SS
Coating	Epoxic

* Silicon Carbide (SiC) optional

REF.	in	mm
A`	17	432
B`	2.8	72
C`	18.2	463
D`	37.1	944
E`	20.6	525

Pump Height		
HP	in	mm
40	51.7	1315
50	56.2	1430
60		

Pump Weight		
HP	Lbs	Kg
40	1058.2	480
50	1278.6	580
60	1322.7	600

REF.	in	mm
A	2.9	76
B	0.3	9
C	3.6	92
D	1.9	50
E	39	992
F	38.1	970
H	20.8	530
H	13.9	355
I	13.7	350
J	2.1	55
K	0.6	16
L	3.2	83
M	46.5	1182
N	5.9	150
O	12.4	317
P	10.2	260
Q	11.4	290
R	5.9	152
S	12.9	328
T	10.8	275
U	23.7	603
V	34.6	880
W	18.5	470
X	11.8	302
Y	30.3	772
Z	47.2	1200

